Email: sales@machinesequipments.com

Product Name:

Food Aseptic Brick Carton Aseptic Filling Machine for 100ml - 330ml

Product Code: MACHEQ-F-M8501001



Description:

Food Aseptic Brick Carton Aseptic Filling Machine for 100ml - 330ml

Technical Specification:

The machine applies to fill milk, fruit juice, coffee, tea drinks, plant protein drinks, wine and a variety of non-carbonated drinks into aseptic cartons, auto-complete feeding, sterilization, filling, forming, packaging in the form of paper aluminum composite cartons to keep long shelf life for safe, fresh, and flavorful without refrigeration or preservatives. The machine uses all stainless steel materials, core components such as the electrical system, pneumatic system, filter screen, and electric control system are carefully selected from well-known branded suppliers in Europe, America and Japan. It is fully automatic controlled by PLC, real human and machine communication through touch screen with different language version. The machine has complete safety guarantee system, got CE certificate, has complete quality control system with complete failure detection system, all the fault can be detected by our machine PLC system, and show the problem solving method on the touch screen. The machine has very high filling accuracy, filing accuracy is only ±1.5%. It's designed with features of simple structure, smooth and efficient operation, easy maintenance, highest possible output, lowest possible operation cost and high food safety. All the machine parts have undergone rigorous testing to bring the performance to an advanced level. Innovative design, high quality components and thorough testing ensures stable and dependable performance at customers site worldwide for dairy, juice beverage and other non-carbonated drinks production.

Name Capacity Filling Volume Dimension Aseptic brick filling machine 7500 packs per hour 100 ml, 125 ml, 160 ml, 200 ml, 220 ml, 250 ml, 4690×2540×3760mm

Connect 2200 mm (W) x 3500 mm (H)

Weight 5000 kg

Electrical 380V±10 %(3?) 50/60Hz

Motor 35 KW

Air consumption 500±100 L/Min(0.6~0.7 MPa);Connect:

Thread 1/2"

Tap water consumption 15 L/M(0.3i½ž0.45 Mpa;? 20â,,f);Thread 1/2"

Steam consumption 4.5 kg/Hi¼^130 ± 5 â, f 〕0.17± 0.03

Mpaï1/4%;Connect:DN25

 H_2O_2 consumption 0.6 $\frac{1}{2}$ 1.0 L/H $\frac{1}{4}$ 30 $\frac{1}{2}$ 50 % $\frac{1}{4}$ %

Control system PLCï¼^HM5)

Discharge conveyor chain

Filling temperature 5â,f~50â,f

Filling Numbers

Packaging forms paper - aluminum composite bricks aseptic brick

shape

Sterile package shelf life the paper aluminum composite film, under normal

temperature 25 $\hat{a}_{,f}$ ~ 30 $\hat{a}_{,f}$, Shelf life is 6

months or more

Access to the air pressure 0.8 Mpa

Machines Equipments Manufacturers

Website: SITE

2/2